

- ☐ Easy to use
- ☐ Self-contained compact encoding/control station (saves space at reception)
- ☐ Compatible with Onity HT22 and HT24W electronic locking systems; connects to PC running Onity HT24W software by means of a RS-485 connection cable
- ☐ Supports MIFARE Classic®/EV1, MIFARE Plus®, MIFARE Ultralight® and MIFARE Ultralight C cards
- ☐ Compatible with any PMS system
- ☐ Incorporates the “uninterrupted key supply” function, which maintains the terminal in operation, should the hotel PMS fail
- ☐ Keeps record of the last 5.000 events
- ☐ Battery back-up
- ☐ Keeps all the hotel cards codes in non volatile memory (as PC back-up)
- ☐ Communication through screen (8 x 20 characters message display)
- ☐ Incorporates 7 hot keys for the most frequently used functions
- ☐ Possibility to work in up to 10 different languages (now English, Spanish, French standard) and able to be adapted to other languages if required
- ☐ Weight: 980 gr.
- ☐ Dimensions: 257 x 165 x 92 mm
- ☐ Power supply: 110 or 220 V
- ☐ Requirements:
  - Power Supply 15V DC / 1 amp
  - RS-232 cable (\*)
  - Win distributor (\*)
  - RS-485 Win distributor connection cable (\*)

(\*) Not needed for HT22 system

